



PointSil™ *Densified Liner*

PointSil™ Densified Liner is a C1S liner designed for demanding heavyweight graphic release applications Utilizing a multitude of silicone curing and adhesive systems. PointSil™ Densified Liner also features scoring and cracking capabilities for fast and precise release on the job site, and is well suited for graphics applications requiring very smooth surfaces. This grade features exceptional dimensional stability for good laminate lay-flat and is well suited for hand peel applications.

FEATURES AND BENEFITS

- Coatings designed for solventless, radiation and emulsion silicones
- Excellent dimensional stability for laminate lay-flat
- Reverse side coated for balanced sheet
- Scoring and cracking capabilities

Caliper	(mils)	3.2	3.8	4.2	4.6
	microns	81	96	107	117
Smoothness	10S, PPS	1.0	1.0	1.0	1.1
Dry Opacity	%	83	85	87	90
Brightness	%	79	80	80	80
MD Tensile	(lbs/in)	36	38	45	51
	N/15mm	95	100	118	134
CD Tear	(grams)	73	68	91	100
	mN	716	667	893	981
Basis Weight	lbs/3000 ft ²	54	60	67	73
	g/m ²	88	98	109	119

MAIN APPLICATIONS

Transportation signage
Indoor and outdoor advertising signage
Other wide format graphic applications

The information given is based upon our knowledge and experience at the time of printing and is given in good faith. It does not represent a guarantee or legal warranty for specific properties or for suitability for a specific use.

Pixelle Specialty Solutions LLC 228 South Main Street, Spring Grove, PA 17362

t: 800.458.6323 www.pixelle.com Rev. 2/25/20