

UNITHERM®

UniTherm® is designed for pressure sensitive thermal transfer applications with conventional pre-print. The coatings on this grade are optimized for thermal transfer printing, while providing a surface for flexographic pre-printing. This grade features a smooth surface and high strength for fast printing and matrix stripping. Reverse side coatings are compatible with pressure sensitive adhesives.

FEATURES & BENEFITS

- ☑ Coatings designed for thermal transfer printing
- ☑ Smooth surface for good bar code reproduction
- ☑ Smudge resistance for durable bar code image
- ☑ High strength for fast matrix stripping
- ☑ High brightness and blue-white shade for good label appearance

BASIS WEIGHT	LBS/3000 FT²	43	45
BASIS WEIGHT	G/M²	70	73
CALIPER	MILS	2.90	3.00
CALIPER	MICRONS	74	74
SMOOTHNESS	5S, PPS	2.00	1.90
OPACITY	%	87	88
BRIGHTNESS	%	85	85
TENSILE CD	LB_F/IN	17	18
TENSILE CD	N/15MM	45	47
TEAR MD	G_F	42	44
TEAR MD	MN	412	432

PXL-36010-080422

The information given is based upon our knowledge and experience at the time of printing and is given in good faith. It does not represent a guarantee or legal warranty for specific properties or for suitability for a specific use.

Contact your Pixelle Sales Representative or call us at Pixelle.

1-800-458-6323 | www.Pixelle.com | CustomerService@Pixelle.com

★★★★★ **USA**
MADE IN THE